

SE-300V PTO POWERED ORCHARD SPRAYER



Standard Feature



Adjustable Air Vanes

Option



Dual Hydraulic Spray Valves



Option

Leaf Guard

Davis & Davis Distributors
507 E. Dinuba Avenue • Reedley, Ca 93654
(Ph)559-638-6546 • (Fax)559-638-9262
Visit us: www.airofan.com • Contact us: info@airofan.com



SE-300V "VOLUTE-TOWER"

PTO DRIVE SPRAYER

STANDARD FEATURES

- 300 Gallon 304 stainless steel tank
- 26 GPM / 600 PSI Comet® diaphragm pump
- 30" diameter, 6-blade axial flow steel fan
- 2 speed gearbox with neutral
- Heavy duty constant velocity PTO shaft
- Tank drive shaft w/ rundown clutch
- 1" 304 stainless steel mechanical agitation
- Cable type remote control
- 304 stainless steel strainers (fill, suction, delivery)
- Teejet® stainless steel nozzles
- Composite nylon adjustable air vanes
- 7.6x15" ribbed implement tires
- Galvanized fan housing
- Vineyard volute tower

OPTIONS

- TeeJet® ceramic nozzles
- Hydraulic and electric control valves
- 2" and 3" Stainless steel fill connections
- Rear leaf guard
- Tire and wheel exchange to 11Lx16.1" 8 ply ribbed tires

SPECIFICATIONS

Length.....13'4"
 Width.....52"
 Height.....55" (top of tank) 75" (top of tower)
 Weight.....1,340 lbs.
 Air Velocity...120 MPH
 PTO Horse Power Requirements...30-60

Visit our website: www.airofan.com

Turning Hitch Options

