

SJ-300 SHORT STACK PTO POWERED 4-RROW BLUEBERRY SPRAYER



Leaf Guard
Option

6,000 Lbs. HD
Hubs & Spindles
Standard Feature



Standard
Feature



Option



Standard Feature

Adjustable Air Vanes

Dual Hydraulic Spray Control Valves

Narrow 52" Tire to Tire!

Davis & Davis Distributors
507 E. Dinuba Avenue • Reedley, Ca 93654
(Ph)559-638-6546 • (Fax)559-638-9262
Visit us: www.airofan.com • Contact us: info@airofan.com



SJ-300 "SLIM JIM" SHORT STACK PTO DRIVE SPRAYER

Spraying

STANDARD FEATURES

- 300 Gallon 304 stainless steel tank
- 26 GPM / 600 PSI Comet® diaphragm pump
- 32" diameter, 7-blade axial flow steel fan
- 2 speed gearbox with neutral
- Heavy duty constant velocity PTO shaft
- Tank drive shaft w/ rundown clutch
- 1" 304 stainless steel mechanical agitation
- Cable type remote control
- 304 stainless steel strainers (fill, suction, delivery)
- 7.50x20" 8 ply ribbed implement tires
- Heavy duty hubs and spindles
- Galvanized fan housing
- Short Stack tower
- Tower has composite nylon adjustable air vanes
- Fan housing has anodized aluminum air vanes
- TeeJet® ceramic nozzles



OPTIONS

- Hydraulic and electric control valves
- 2" and 3" Stainless steel fill connections
- Rear leaf guard
- DK turning & 2-Point turning hitch

SPECIFICATIONS

Length.....13'4"

Width.....52"

Height.....55" (Top of Tank) 94" (Tower Top)

Weight.....1,840 lbs.

Air Velocity...120 MPH

PTO Horse Power Requirements...35-65



Visit our website: www.airofan.com

DK Operating

2-Pt. Operating